PURUS PLASTICS



Ground Reinforcement System

ECORASTER® Bloxx

Specifications

ECORASTER® Bloxx – The New Block Paver

For fast installation of permeable ground reinforcement with concrete paver design



Technical Data

Dimensions:	330 mm x 330 mm x 50 mm 12.99 X 12.99 x 1.97 inches
Weight:	approx. 85 kg| 187.39 lbs (incl. blocks)
Locking System:	36 T-elements /m² 6 T-elements/ sqft
Dimensional Stability (Temperature):	-50° to +90 ° C -58° F to +194°F
Block Dimensions:	140 x 140 x 45mm (each) 5.51 x 5.51 x 1.77 inches
Weight per Block:	approx. 2.12 kg| 4.67 lbs
Available Colours:	red, white, dark grey and light grey

Delivery units

Transport variations	VPE 1	VPE 2
Conrete blocks per pallet:	260 pcs.	520 pcs.
ECORASTER® Bloxx modules per pallet:	65 pcs.	130 pcs.
Area per pallet:	7,22 (m²) 77.68 sqft	14,44 (m²) 155.37 sqft
Weight per pallet (approx):	625 kg 1.377,88 lbs	1.235 kg 2.722,70 lbs
Other picking and packing available on request.		

Note: Please follow our installation instructions and guidelines available on our website.

Take advantage of our years of experience and technical know-how, which we implement daily in desing and manufacturing of our quality products.

QUALITY made in GERMANY

The advantages

- ✓ Permeable Ground Rainforcment
- ✓ Variable and Flexible Applications
- ✓ Heavy load
- ✓ High rate of installation
- ✓ Proven Safety Locking System
- ✓ Fits seamlessly in all ECORASTER®Systems
- ✓ Resistant to UV and aggressive solvents
- ✓ Easy maintainance, long-lasting
- ✓ Made in Germany
- ✓ Environmentally Neutral
- ✓ 100% Recycled Content

Applications

- » Parking lots
- » Universal Accessibility
- » Driveways
- » Pedestrian and bicycle paths

Accessories

PURUS offer accessories for ECORASTER® ground reinforcement systems, including hinge and curve adaptors as well as parking markers.

PURUS PLASTICS

Purus North America Inc.
1790 Avenue Road Unit A
M5M 3Z1 Toronto

Tel.: 800 495 5517

www.ecoraster.us
www.ecoraster.ca

ECORASTER® is a Trademark of PURUS PLASTICS GmbH